


Load carrier with tip - Park Ranger 2150



1015 mm



2440 mm

1210 mm
1935 mm

Standard equipment:

- Hydraulic tipping** The hydraulic tipping action makes it fast and easy to empty the load carrier with tip.
- Removable sides** The volume can be adjusted with the removable sides.
- Lockable back flap** The back flap can be locked in the horizontal position to allow for the transportation of planks, garden tools etc.
- Stand** The supplied stand allows for simple and quick fitting and removal of the load carrier with tip. One person can therefore easily attach / detach the load carrier with tip alone.

Technical specifications

Dimensions

| | | |
|-----------------------------|----|-------------|
| Length | mm | 2440 |
| Width | mm | 1015 |
| Height with / without cabin | mm | 1935 / 1340 |

Storage dimensions

| | | |
|--------|----|------|
| Length | mm | 1400 |
| Width | mm | 950 |
| Height | mm | 1350 |

Weights

| | | |
|---|----|-----------|
| Weight with / without cabin ¹⁾ | kg | 770 / 660 |
| Payload with / without cabin | kg | 530 / 640 |
| Weight (load carrier with tip) | kg | 138 |

Performance

| | | |
|------------------------------|----------------|----------|
| Platform, length | mm | 1040 |
| Platform, width | mm | 860 |
| Platform, height | mm | 300/600 |
| Volume | m ³ | 0,4 |
| Load carrying capacity, max. | kg | 300 |
| Loading height | mm | 700-1040 |

CE certified according to EU directive

¹⁾ Includes: load carrier, 75 kg operator and 90% fuel capacity.

