

Suction sweeper

- City Ranger 2260



Standard equipment:

- Hopper** As standard the hopper has a rotation filter system and a fresh water tank with 100 l capacity.
- Front brush unit** The standard unit consists of two front brushes, each particular fitted with a water nozzle and a suction mouth. This newly developed suction mouth has been designed with fewer mechanical parts for lower operation and maintenance costs. New shutter system ensures maximum vacuum while minimizing the risk of clogging.
- Nose wheel** To adjust height of brushes.
- Hopper stand** The stand for attaching, detaching and storing the hopper allows you to attach/detach the hopper in just 1 minute supporting the multi-functionality of the machine.
- Water meter / indicator** There is a water meter on the side of the hopper and a water indicator in the cabin. They ensure an excellent overview over your water consumption and capacity.
- Wander hose** The wander hose system is handy for areas out of reach of the suction sweeper unit. With easy access, great mobility and excellent suction performance, cleaning tasks around park bins, benches, steps, tress and other obstacles can be done in no time and with good results. Specifications: 5 m x Ø150 mm.

Extra equipment (options):

- 3rd and/or 4th brush** The suction sweeper can be equipped with 2-4 brushes - the two front brushes are standard and the two side brushes are optional extras. Each brush is equipped with a water sprayer to prevent dust spreading while the unit is working. The front brushes are height-adjustable via a nose wheel.
- High pressure washer** An integrated high-pressure cleaner with a capacity of approx. 100 bar and 6.5 l/min. as an option. With the ergonomic lance and a hose length of approx. 6 meters, it is suitable for cleaning signs, park benches, waste bins and the like, but also for cleaning the machine itself.
- Suction nozzle with centre brush** As an alternative to the newly developed suction mouth, it is possible to buy the suction sweeper with Egholm's regular suction mouth with centre brush.

Technical specifications

| Dimensions | | |
|---|-------------------|-------------|
| Length | mm | 2820 |
| Width | mm | 1200 |
| Height with cabin / roll bar (ROPS) | mm | 1939 / 2060 |
| Length with 3 rd and 4 th brush | mm | 3400 |
| Width with 3 rd and 4 th brush | mm | 2100 |
| Storage dimensions | | |
| Length | mm | 900 |
| Width | mm | 1100 |
| Height | mm | 600 |
| Weights | | |
| Weight with cabin ¹⁾ | kg | 1205 |
| Payload with cabin | kg | 405 |
| Weight - hopper | kg | 179 |
| Weight - front brushes, 2 brushes | kg | 79 |
| Weight - 3 rd or 4 th brush | kg | 22 |
| Hopper | | |
| Hopper net volume (EN 15429-1) | l | 450 |
| Hopper gross volume | l | 546 |
| Hopper load, max. | kg | 300 |
| Tipping height | mm | 1300 |
| Fresh water tank capacity | l | 100 |
| Sweeping system & performance | | |
| Working width - 2 brushes | mm | 1200 |
| Working width up to - 3 rd / 4 th brush | mm | 1650 / 2100 |
| Turning circle - 2 brushes and hopper (wall to wall) (EN 15429-1) | mm | 3520 |
| Turning circle - 3/4 brushes and hopper (wall to wall) (EN 15429-1) | mm | 4500 |
| Brush speed | rpm | 0-100 |
| Brush diameter Ø | mm | 570 |
| Suction tube diameter Ø | mm | 150 |
| Ground clearance below suction mouth | mm | 55 |
| Ground clearance below brushes | mm | 140 |
| Air flow | m ³ /h | 2700 |
| Air speed | km/h | 155 |
| Noise level LwA (2000/14/EC) | dB(A) | 106 |
| Dust levels: EUnited PM10 and PM2.5 | | **** |
| CE certified according to EU directive | | |

¹⁾ Includes: hopper, 2 brushes, 75 kg operator and 90% fuel capacity.

