



Robust scrubber dryer RA605-2

RA605-2



Shapely, robust scrubber dryer, ideal for hard and flexible floors for industries, retail and public environments. Two contra-rotating brushes for streak-free cleaning. Automatic traction, as well as environmentally friendly chemical dosing with the Cleanfix-Dosing-System (optional), ensures a high user friendliness. Ideal for bigger surfaces.





Technical data:

| Power supply | 24 V DC |
|-------------------------------|---------------|
| Power brush motor | 750 W |
| Power suction motor | 400 W |
| Vacuum | 130 mbar |
| Fresh water capacity | 55 |
| Dirty water capacity | 56 |
| Suction width | 88 cm |
| Working width | 62 cm |
| Productivity rate theoretical | 2500 m²/h |
| Brush pressure | 57 kg |
| Weight without batteries | 113 kg |
| Weight incl. batteries | 190 kg |
| Measurements I/w/h | 138/64/113 cm |













Special accessories:

565.565A Suction nozzle curved

Complete incl.:

565.059

| opeciai a | GGG33011G3. |
|-----------|---|
| 530.091 | Set of 2 Gel batteries à 12 V / 105 Ah |
| | (C5) (345 x 172 x 283 mm) |
| 681.004 | Filling up hose for fresh water, 1,6 m |
| 565.535 | Canister 5 I empty |
| 705.610 | Supper Gripp wheel |
| 565.081 | Rubber blade oil resistant |
| 565.080LT | Rubber blade, standard |
| 565.070 | Driving disc (2 pieces needed) |
| 693.052.5 | Pad red (5 pieces) |
| 693.053.5 | Pad blue (5 pieces) |
| 693.054.5 | Pad brown (5 pieces) |
| 565.0595K | Scrubbing brush 5K (2 pieces needed) |
| 565.073 | Exposed aggregate pavement brush |
| | (2 pieces needed) |
| 565.074 | Exposed aggregate pavement brush, fine |
| | (2 pieces needed) |
| 565.076 | Silicium Carbid brush (2 pieces needed) |

Scrubbing brush (2 pieces needed)



Suction unit and brush head lifting by foot



Switzerland

Cleanfix Reinigungssysteme AG Stettenstrasse 15 | 9247 Henau-Uzwil/SG Tel. +41 71 955 47 47 | Fax +41 71 955 47 60 info@cleanfix.com